



DB200SSL

DOLPHIN INFRARED TOUCH FREE TAP

- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Special Finishes: PPC in all RAL colours, Mirror Polished or 316 Stainless Steel
- › Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- › Tap settings including optional hygiene flush can be adjusted by using remote control (DB51)
- › 2 year manufacturer's warranty
- › Water supply: Single - cold or premixed
- › Mandatory Hygiene Flush feature to combat risks of legionnaire
- › The hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control. Taps are supplied with this feature switched on.
- › Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
- › Power Source: 9 Volt Battery / Plug-in 9 Volt transformer
- › Power connections: tap: male / power source: female
- › 3/8" BSP water supply connector
- › Maximum water temperature 70°C
- › Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- › Counter Hole: diameter 28-34mm, minimum/maximum thickness: 2-27mm
- › Complies with SKA rating criteria
- › WRAS Approved product
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT1 credits.

HEIGHT	142MM
DIAMETER	50MM
PROJECTION	95MM

PRODUCT CODES

- DB200C-SSL** - Battery powered polished finish
- DB225C-SSL** - Transformer powered polished finish

