



DB840 / DB845

DOLPHIN ELECTRONIC INFRARED TAP

- > WRAS approved product
- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Polished chrome plating or brushed nickel plating
- > Water Supply: Single inlet – cold or pre-mixed
- > A TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
- > Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- > 3/8" BSP water supply connector
- > To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on
- > 2 year manufacturer's warranty
- > Complies with SKA rating criteria
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this tap
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits
- > Power Source: Plug-in 9 Volt transformers or 9 Volt Battery (with low battery warning)
- > Counter Hole: diameter 28-34mm
- > Minimum/maximum counter thickness: 2-27mm

HEIGHT	157MM
DIAMETER	45MM
PROJECTION	122MM

PRODUCT CODES

- DB840S** - Battery powered brushed finish
- DB840C** - Battery powered, polished finish
- DB845S** - Transformer powered, satin finish
- DB845C** - Transformer powered, polished finish

