





## DBL200 / DBL225

## DOLPHIN COUNTER MOUNTED ELECTRONIC INFRARED TAP

- > Touch Free Electronic Tap Tap is activated when the user brings hands within the state of the art electronic infrared sensor Designed for counter top basins
- > Quality polished chrome plated brass finish from stock also available in ceramic and powder coated finishes
- > Ultimate Hygiene-Prevents cross contamination
- > Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
- > Flow time once user's hands are removed from the tap I second (adjustable by using remote control DB51)
- > Filters, fixing bolts, installation instructions and power source supplied with each tap
- > 2 year manufacturer's warranty
- > Hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on
- > WRAS Approved product, complies with SKA rating criteria
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this Dolphin Blue tap
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT I credits.
- > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits
- $\scriptstyle >$  Counter: Hole : diameter 34-36mm : Min-Max counter thickness: 2-27mm
- > Water Supply: Single inlet cold or pre-mixed water supply 3/8" BSP Water supply connection
- > Power Source: 9 Volt Battery pack/Plug in transformers

HEIGHT 338MM DIAMETER 44MM PROJECTION 106MM

## PRODUCT CODES

**DBL225C** - Battery powered, polished finish **DBL225C** - Transformer powered, polished finish

**DBL200.5.xx** - Battery powered, powder coated finish

**DBL225.5.xx** - Transformer powered, powder coated finish

**DBL200.6.xx** - Battery powered, ceramic coated finish

**DBL225.6.xx** - Transformer powered, ceramic coated finish



**SKA**rating



