



BC1032

DOLPHIN WALL MOUNTED SOAP DISPENSER

- > Superior quality and timeless design for prestigious washrooms
- > Designed for heavy traffic prestigious environments
- > Solid brass construction with brushed satin plating
- > Soap feeds via a flexible tube (various lengths to order up to a maximum recommended length of 2m) to a container of your choice (ordered separately)
- > Supplied with 2m of flexible feed tube
- > Where several dispensers are installed together our multi-feed system is recommended: BC1900MA and BC1900MB
- > Can be installed into panels up to 55mm thick – hole diameter through panel 19mm
- > Can be used with Standard Liquid Hand Soap and Anti Bacterial Soap
- > Suitable for pressurised soap systems (including gravity fed)
- > This dispenser can be maintained from the front, no rear access is required.

DIAMETER	25 MM
PROJECTION	120 MM

PRODUCT CODES

- > **BC1032B** Polished Chrome Brass
- > **BC1032-316** Brushed Satin Stainless Steel Grade 1.4401 (316)

OPERATION

- › Press plunger head towards dispenser body to dispense soap into palm of hand. Each stroke delivers approximately 1ml of liquid soap per activation. Recommended for high traffic use areas. Use with multi-feed system

INSTALLATION KIT

- › Prepare a Ø19mm mounting hole through wall
- › Detach the push fit elbow
- › Unscrew the locking nut and remove it and the washers from the soap dispenser assembly
- › Pass tail of soap dispenser through the mounting hole
- › Re-fit stainless steel washer and locking nut and tighten locking nut
- › Tighten grub screws on washer into the wall
- › Re-fit push fit elbow
- › Connect multi-feed tube to tube adaptor
- › Prime the soap dispenser using syringe supplied, or by pumping the plunger head liquid soap is dispensed from the nozzle

CARE AND MAINTENANCE

- › If the soap dispenser fails to function correctly, firstly check all connections are tight and free from air leaks. If dispenser still fails to function, place manifold into a bottle of warm water. Pump the warm water through the dispenser to dislodge any dried soap residue and then refit manifold into soap bottle.
- › Water marks and soap residue on polished chrome surfaces are best cleaned using warm water and a mild detergent. Use a stainless steel cleaner for brushed stainless steel soap dispensers. Never use an abrasive cloth to remove stubborn stains. Dry with a soft clean cloth.

WARRANTY

This product is covered by a 12-month warranty from the date of purchase to be free from defects if installed and maintained in accordance with these instructions. Dolphin Solutions will replace or repair (as appropriate) free of charge any product with a proven manufacturing defect if reported within the warranty period.

We do not recommend using high viscosity liquid soaps or gels, or washing up liquid which may impair function.

***Warning:** Liquid with high sodium chloride content can cause corrosion and may invalidate the product warranty.

Dolphin Solutions Ltd reserves the right to amend the design or dimensions without formal notice.