







DB3100 DOLPHIN BLUE SHOWER VALVE

> Dolphin Blue Shower Valve with Thermostatic Temperature Control and Two-Ways Diverter

> Minimalist design with slimline rectangular face plate

> TMV3 thermostatic temperature control maintains consistent, comfortable showering temperature whilst ensuring against scalding

> 30mm levers on the DB3100 version (As shown above) allow operation even with a clenched fist ideal for installation in accessible areas

> Two outlets (two-ways diverter) for connection to an fixed shower head and hand held shower head with hose (sold separately)

> Single outlet (headworks) also available for either fixed shower head OR hand held shower head with hose – see DB3200

> Complements most of our other Dolphin taps and fittings

> Available in both Satin and Chrome finishes

> High quality brass and stainless steel construction with highest quality cartridges and mechanisms from market leading specialist manufacturers from within Europe to ensure robust and reliable

performance in high demand commercial locations

> Suitable for all water systems > 5 year parts and labour guarantee

 WIDTH
 I 30MM

 HEIGHT
 215MM

 PROJECTION
 45MM

Note: To obtain an optimum function (regulation in conformance with the standards, absence of noise or hydraulic vibrations), we recommend a limiting of the hot/cold inlet pressures to 5 bar, with a difference of pressure between hot and cold not exceeding 2 bar. This pressure should be a constant (therefore the dynamic rather than static pressure) and avoid pressure fluctuations caused by pumps cycling.



TECHNICAL HELPLINE 01424 202224 DOLPHINSOLUTIONS.CO.UK