



DS211
DOLPHIN SLIMLINE INFRARED BASIN TAP

- > Dolphin Up and Over Thru Counter Mounted Inform Tap
- > Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel
- > Self-monitoring analysis and recording technology (smart) allows the Facilities Manager to connect point to point via the Dolphin Inform App when used with the optional Bluetooth Adaptor (Sold separately – Order product code 25148)
- > 90° spout
- > Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination – sensor mounted in end of spout
- > Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 4, 3, 2, 1.75, and 1LPM flow rates on special request
- > Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for pre-mixed applications
- > Maximum operating water temperature - 60°C
- > Nominal current: Less than 1mA (Less than 25mA with Bluetooth)
- > Nominal power: Less than 1W
- > Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- > IP68 connector
- > Power Source: Plug-in 9 Volt transformers, Hardwire transformers, or battery packs
- > WRAS approved
- > Comes with laminar flow feature to avoid splashing
- > Comes as standard with 24 hour line purge/hygiene flush feature, with alterable timings

HEIGHT	150/200MM
PROJECTION	150/200MM
DIAMETER	22MM



NOTE: Highly reflective surfaces directly beneath the sensor of this product, in particular polished finish basin wastes/strainers, will cause false activation of the infrared sensors and cause malfunction.