



Certificate number: 2405724 (1)

Issued 31/05/2024

Expires 31/05/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Dolphin Solutions Limited.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Dolphin Solutions Limited
Southpoint
Compass Park
East Sussex
TN32 5BS
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2405724

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Range of wall mounted electronically operated tap assemblies (stainless steel bodies). The flow is controlled by a solenoid valve and actuated via an infra-red sensor. The spout outlet incorporates a plastic aerator. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) DS101.bbb.d. ee DS102.bbb.d. ee DS103.bbb.d. ee DS104.bbb.d. ee</p> <p>Where the model code can be derived from: DSaaa.bbb.d. ee 'aaa' denotes the style type, the following options are available: DS101 - 90° bent spout, DS102 - 90° bent spout with wall plate fixing kit, DS103 - 55° bent spout or DS104 - 55° bent spout with wall plate fixing kit.</p> <p>'bbb' denotes the projection of the spout from wall to spout outlet in mm. Range 107mm – 330mm.</p> <p>'d' denotes the surface finish (which is a non-water contact part). It will always be 1 digit and either a letter or numbers. As examples: 1 = brushed satin stainless steel, 3 = PVD coated brushed satin stainless steel.</p> <p>'ee' denotes the surface colour (which is a non-water contact part) where applicable. It will always be 2 digits, which can be any combination of numbers and/or letters. As examples: 01 = RAL9005 Black, 51 = PVD Gold finish</p> <p>Models may include an additional '.R' suffix which denotes that the tap is supplied without the rosette, or an additional 'fff' suffix to denote a non-standard size Rosette (which is a non-water contact part) It will always be 2-3 digits, which can be any combination of numbers and/or letters</p>
<p>SIZE: ½" BSP(M).</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 6 Bar & maximum operating temperature 65°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 65°C.</p>
<p>MARKING Dolphin logo under body of tap.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES Consideration must be made on installation to the airgap arrangement.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes