



C sections are supplied loose and are **ONLY** required if the unit is to be used with either the BC28-1SCA or the BC28-3SCA

BC28-2SCA

ECO SLIMLINE RECESSED HAND DRYER

- › Quality Satin Stainless Steel fascia
- › Replaces the BC27-2SCA
- › Motor only 420-500W (adjustable)
- › Heater element 420-500W (adjustable and with an on/off switch facility)
- › Combined power output 840-1000W
- › Ultra-slim recessed hand-dryer – only 88mm recess depth and projection of 16mm
- › Infra-red, self adjusting sensor
- › Sound Level 72.8 dB minimum to 77.6 dB maximum, adjustable
- › IP24 rated and Class I rated isolation
- › Dryer delivers 105 m³/hour
- › This dries hands within 15 seconds, reducing the CO₂ emissions
- › 22,000 - 29,000 rpm brush motor – air speed adjustable (slower speed makes running quieter)
- › Operating power consumption less than 5 amps at 230V
- › Stand by power less than 0.5W
- › 3 year manufacturers warranty
- › Outlet temperature 55°C (131°F) at 25°C (77°F) ambient temperature
- › Average Reuse Rate under WEEE Directive: 78%
- › Average Recovery Rate under WEEE Directive: 96%
- › Ska compliant product
- › Use in conjunction with BC 28-1SCA and BC28-3SCA

HEIGHT	400MM
WIDTH	320MM
PROJECTION	16MM

SKArating®

PLEASE NOTE: We strongly recommend that the surfaces beneath and to either side of this dryer allow regular cleaning (such as smooth cleanable paint, tile, Perspex, stainless steel etc) to prevent staining from the water blown from users hands. New generation high speed dryers such as this are designed to blow the water off the hands so consideration like this needs to be given to deal with the water deposits.

TECHNICAL HELPLINE 01424 202224
DOLPHINSOLUTIONS.CO.UK