



DS241

DOLPHIN INFORM 90 DEGREE SWAN NECK TAP

- › Dolphin Counter Mounted InForm (SMART) 90 degree Swan neck Tap
- › Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel.
- › Self-Monitoring Analysis and Recording Technology (SMART) allows the Facilities Manager to connect point to point via the Dolphin SMART App when used with the optional Bluetooth Adaptor (Sold separately -Order product code 25148)
- › Infra-Red Touch FreeTap for ultimate hygiene prevents cross contamination
- › Sensor mounted in the spout of the tap, not in the body or external
- › Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25 and 1.75LPM flow rates on special request
- › Water Supply: Single inlet cold or pre-mixed aTMV2 orTMV3 thermostatic mixing valve is recommended for premixed applications
- › Maximum operating water temperature - 60°C
- › Nominal Current: Less than 1mA (Less than 25mA with Bluetooth)
- › Nominal Power: Less than 1W
- › Security Time can be adjusted via the App Default 20 Seconds (60 Seconds max)
- › IP68 Connector
- › Manufactured in the UK
- › Available with a laminar flow option instead of standard aerator

DIAMETER	22MM
HEIGHT	275MM
PROJECTION	150/200MM

PRODUCT CODES

- DS241.150.275** - 90 degree Swan Neck Smart Tap, 150mm projection, 275mm height
- DS241.200.275** - 90 degree Swan Neck Smart Tap, 200mm projection, 275mm height
- DS243.150.275** - 55 degree Swan Neck Smart Tap, 150mm projection, 275mm height
- DS243.200.275** - 55 degree Swan Neck Smart Tap, 200mm projection, 275mm height



WELL